

Klipper

- [Ender 2 pro printer.cfg](#)
- [StartStopPrinter.cfg](#)
- [macro.cfg](#)

Ender 2 pro printer.cfg

```
[include mainsail.cfg]
[include macros/*.cfg]

[virtual_sdcard]
path: /home/biqu/printer_data/gcodes
on_error_gcode: CANCEL_PRINT

[mcu]
serial: /dev/serial/by-id/usb-Klipper_XXXXXXXXXXXXXXXX

[printer]
kinematics: cartesian
max_velocity: 300
max_accel: 3000
max_z_velocity: 5
max_z_accel: 100

#####
# "RepRapDiscount 128x64 Full Graphic Smart Controller" type displays
#####

[board_pins]
aliases:
    # EXP1 header
    EXP1_1=PD5, EXP1_3=PB3, EXP1_5=PB5, EXP1_7=PB7, EXP1_9=<GND>,
    EXP1_2=PD4, EXP1_4=PD6, EXP1_6=PB4, EXP1_8=PB6, EXP1_10=<5V>,
    # EXP2 header
    EXP2_1=PB14, EXP2_3=PB8, EXP2_5=PC10, EXP2_7=PC12, EXP2_9=<GND>,
    EXP2_2=PB13, EXP2_4=PB9, EXP2_6=PB15, EXP2_8=<RST>, EXP2_10=<NC>

[display]
lcd_type: st7920
cs_pin: EXP1_4
sclk_pin: EXP1_5
sid_pin: EXP1_3
```

```
encoder_pins: ^EXP2_3, ^EXP2_5
```

```
click_pin: ^!EXP1_2
```

```
#kill_pin: ^!EXP2_8
```

```
[output_pin beeper]
```

```
pin: EXP1_1
```

```
#####
```

```
# Temperature Sensors
```

```
#####
```

```
[temperature_sensor CB1]
```

```
sensor_type: temperature_host
```

```
min_temp: 10
```

```
max_temp: 100
```

```
[temperature_sensor M5P]
```

```
sensor_type: temperature_mcu
```

```
min_temp: 10
```

```
max_temp: 100
```

```
#####
```

```
# Fan configuration
```

```
#####
```

```
[heater_fan HotendFan]
```

```
pin: PA3
```

```
max_power: 1.0
```

```
fan_speed: 1.0
```

```
kick_start_time: 0.1
```

```
heater: extruder
```

```
heater_temp: 50.0
```

```
[fan]
```

```
pin: PA4
```

```
#[heater_fan SoC_fan]
```

```
#pin: cb1:gpio79
```

```
#####
```

```
# BLTouch Sensors
```

```
#####
```

```
[bltouch]
```

```
sensor_pin: PC13
```

```
control_pin: PC15
```

```
samples: 2
```

```
#horizontal_move_z: 10
```

```
speed: 20
```

```
x_offset: -41
```

```
y_offset: -8
```

```
#z_offset: 0.0
```

```
#####
```

```
# Bed Mesh Settings
```

```
#####
```

```
[bed_mesh]
```

```
speed: 100
```

```
horizontal_move_z: 10
```

```
mesh_min: 10, 5
```

```
mesh_max: 113, 135
```

```
probe_count: 4, 4
```

```
mesh_pps: 2,2
```

```
fade_start: 1
```

```
fade_end: 10
```

```
fade_target: 0
```

```
#####
```

```
# NeoPixel configuration
```

```
#####
```

```
[neopixel Licht]
```

```
pin: PC11
```

```
chain_count: 1
```

```
initial_RED: 0.0
```

```
initial_GREEN: 1.0
```

```
initial_BLUE: 0.0
```

```
initial_WHITE: 0.0
```

```
#####  
# X-Axis configuration  
#####
```

```
[stepper_x]  
step_pin: PC8  
dir_pin: !PC9  
enable_pin: !PA15  
microsteps: 16  
rotation_distance: 40  
endstop_pin: ^PD3  
position_endstop: 0  
position_max: 155  
homing_speed: 50
```

```
[tmc2209 stepper_x]  
uart_pin: PD9  
run_current: 0.800  
diag_pin: PD3  
stealthchop_threshold: 999999
```

```
#####  
# Y-Axis configuration  
#####
```

```
[stepper_y]  
step_pin: PA10  
dir_pin: !PA14  
enable_pin: !PA13  
microsteps: 16  
rotation_distance: 40  
endstop_pin: ^PD2  
position_endstop: 0  
position_max: 150  
homing_speed: 50
```

```
[tmc2209 stepper_y]  
uart_pin: PD8  
run_current: 0.800
```

```
diag_pin: PD2
stealthchop_threshold: 999999
```

```
#####
# Z-Axis configuration
#####
```

```
[stepper_z]
step_pin: PC6
dir_pin: PC7
enable_pin: !PA9
microsteps: 16
rotation_distance: 8
#endstop_pin: ^PC3
endstop_pin: probe:z_virtual_endstop
#position_endstop: 0.0
position_max: 170
position_min: -2.0
```

```
[tmc2209 stepper_z]
uart_pin: PB10
run_current: 0.800
diag_pin: PC3
stealthchop_threshold: 999999
```

```
[safe_z_home]
home_xy_position: 117,85 # Change coordinates to the center of your print bed
speed: 50
z_hop: 10 # Move up 10mm
z_hop_speed: 5
```

```
#####
# Extruder configuration
#####
```

```
[extruder]
step_pin: PB12
dir_pin: PB11
enable_pin: !PA8
microsteps: 16
```

```
#rotation_distance: 33.500
rotation_distance: 23.467
nozzle_diameter: 0.400
filament_diameter: 1.750
heater_pin: PC5
sensor_type: EPCOS 100K B57560G104F
sensor_pin: PA1
#control: pid
#pid_Kp: 21.527
#pid_Ki: 1.063
#pid_Kd: 108.982
min_temp: 0
max_temp: 270
```

```
[tmc2209 extruder]
uart_pin: PB2
run_current: 0.800
diag_pin: PC2
stealthchop_threshold: 999999
```

```
#####
# Bed configuration
#####
```

```
[heater_bed]
heater_pin: PA5
sensor_type: Generic 3950
sensor_pin: PA0
#control: watermark
min_temp: 0
max_temp: 130
```

StartStopPrinter.cfg

```
#####  
## Start print macro  
#####  
  
[gcode_macro START_PRINT]  
gcode:  
  # Get Params  
  {% set t_extruder = params.T_EXTRUDER|default(205)|float %}  
  {% set t_bed = params.T_BED|default(60)|float %}  
  {% set b_min_x = params.BUILD_MIN_X|default(10)|float %}  
  {% set b_min_y = params.BUILD_MIN_Y|default(10)|float %}  
  {% set b_max_x = params.BUILD_MAX_X|default(133)|float %}  
  {% set b_max_y = params.BUILD_MAX_Y|default(145)|float %}  
  
  #Set LED Red  
  SET_LED LED="Licht" Red=1 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1  
  
  M117 Bett heizt  
  
  # Start  
  M140 S{t_bed} ; Setze Heatbed Temperatur  
  M190 S{t_bed} ; Warte auf Bed Zieltemperatur  
  
  #Set LED Blue  
  SET_LED LED="Licht" Red=0 GREEN=0 BLUE=1 SYNC=0 TRANSMIT=1  
  
  M117 Home xyz  
  
  G28 ; Home  
  M83 ; Extruder relativer Modus  
  
  M117 Kallibrierung
```

```

# Start probing
#BED_MESH_CALIBRATE PROFILE=mesh1 METHOD=automatic
BED_MESH_CALIBRATE AREA_START={b_min_x},{b_min_y} AREA_END={b_max_x},{b_max_y}

G1 X5 Y5 Z15 F2200
#G1 Z0.2 F3000
G92 E0.0 ; Extruder Reset
G90 ; Absolute Positionierung

#Set LED Red
SET_LED LED="Licht" Red=1 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1

M117 Hotend heizt

M104 S{t_extruder} ; Setze Hotend Temperatur
M109 S{t_extruder} ; Warte auf Hotend Zieltemperatur

#Set LED White
SET_LED LED="Licht" RED=1 GREEN=1 BLUE=1 SYNC=0 TRANSMIT=1

# _PRIME_LINE;macro

G1 E8 F2000
G1 Z0.3 F3000 ; put down hotend
G1 X5 Y5 F2200

M82 ; Absolute Positionierung
G92 E0 ;zero the extruded length again

M117 Druck aktiv

#####
## End print macro
#####

[gcode_macro PRINT_END]
gcode:
TURN_OFF_HEATERS
G91 ; Relative Position

```

```
G1 E-5 F3000 ; Retract
G1 X-0.5 Y-0.5 E-5
G90 ; Absolute Positionierung
G1 X83 Y145 F2200 ; Bewege den Kopf nach hinten in die Mitte
M107 ; Partcooling Fan deaktivieren
M84
M117 Druck fertig
```

```
#Turn LED off
```

```
SET_LED LED="Licht" RED=0 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1
```

```
NOTIFY_PRINT_DONE
```

```
#####
```

```
## Prime Line macro (not in use)
```

```
#####
```

```
[gcode_macro _PRIME_LINE]
```

```
gcode:
```

```
G90 ; Absolute Position
G1 E10 F2000
G1 Z0.3 F3000 ; put down hotend
G1 X5 Y5 F2200
G1 X5 Y5 Z0.2 F3000 ; get ready to prime
G92 E0 ; reset extrusion distance
G1 X110 E15 F600 ; prime nozzle
G1 X140 F5000 ; quick wipe
```

```
#####
```

```
## Mesh probe macro (not in use)
```

```
#####
```

```
[gcode_macro probe_mesh]
```

```
gcode:
```

```
# Set extruder and bed temperature
M190 S60
# Home all axis
G28
# Start probing
BED_MESH_CALIBRATE PROFILE=mesh1 METHOD=automatic
```

```
# Turn off heaters afterward
```

```
TURN_OFF_HEATERS
```

macro.cfg

```
#####  
## Start print macro  
#####  
  
[gcode_macro START_PRINT]  
gcode:  
  # Get Params  
  {% set t_extruder = params.T_EXTRUDER|default(205)|float %}  
  {% set t_bed = params.T_BED|default(60)|float %}  
  {% set b_min_x = params.BUILD_MIN_X|default(10)|float %}  
  {% set b_min_y = params.BUILD_MIN_Y|default(10)|float %}  
  {% set b_max_x = params.BUILD_MAX_X|default(133)|float %}  
  {% set b_max_y = params.BUILD_MAX_Y|default(145)|float %}  
  
  #Set LED Red  
  SET_LED LED="Licht" Red=1 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1  
  
  M117 Bett heizt  
  
  # Start  
  M140 S{t_bed} ; Setze Heatbed Temperatur  
  M190 S{t_bed} ; Warte auf Bed Zieltemperatur  
  
  #Set LED Blue  
  SET_LED LED="Licht" Red=0 GREEN=0 BLUE=1 SYNC=0 TRANSMIT=1  
  
  M117 Home xyz  
  
  G28 ; Home  
  M83 ; Extruder relativer Modus  
  
  M117 Kallibrierung
```

```

# Start probing
#BED_MESH_CALIBRATE PROFILE=mesh1 METHOD=automatic
BED_MESH_CALIBRATE AREA_START={b_min_x},{b_min_y} AREA_END={b_max_x},{b_max_y}

G1 X5 Y5 Z15 F2200
#G1 Z0.2 F3000
G92 E0.0 ; Extruder Reset
G90 ; Absolute Positionierung

#Set LED Red
SET_LED LED="Licht" Red=1 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1

M117 Hotend heizt

M104 S{t_extruder} ; Setze Hotend Temperatur
M109 S{t_extruder} ; Warte auf Hotend Zieltemperatur

#Set LED White
SET_LED LED="Licht" RED=1 GREEN=1 BLUE=1 SYNC=0 TRANSMIT=1

# _PRIME_LINE;macro

G1 E8 F2000
G1 Z0.3 F3000 ; put down hotend
G1 X5 Y5 F2200

M82 ; Absolute Positionierung
G92 E0 ;zero the extruded length again

M117 Druck aktiv

#####
## End print macro
#####

[gcode_macro PRINT_END]
gcode:
TURN_OFF_HEATERS
G91 ; Relative Position

```

```
G1 E-5 F3000 ; Retract
G1 X-0.5 Y-0.5 E-5
G90 ; Absolute Positionierung
G1 X83 Y145 F2200 ; Bewege den Kopf nach hinten in die Mitte
M107 ; Partcooling Fan deaktivieren
M84
M117 Druck fertig
```

```
#Turn LED off
```

```
SET_LED LED="Licht" RED=0 GREEN=0 BLUE=0 SYNC=0 TRANSMIT=1
```

```
NOTIFY_PRINT_DONE
```

```
#####
```

```
## Prime Line macro (not in use)
```

```
#####
```

```
[gcode_macro _PRIME_LINE]
```

```
gcode:
```

```
G90 ; Absolute Position
G1 E10 F2000
G1 Z0.3 F3000 ; put down hotend
G1 X5 Y5 F2200
G1 X5 Y5 Z0.2 F3000 ; get ready to prime
G92 E0 ; reset extrusion distance
G1 X110 E15 F600 ; prime nozzle
G1 X140 F5000 ; quick wipe
```

```
#####
```

```
## Mesh probe macro (not in use)
```

```
#####
```

```
[gcode_macro probe_mesh]
```

```
gcode:
```

```
# Set extruder and bed temperature
M190 S60
# Home all axis
G28
# Start probing
BED_MESH_CALIBRATE PROFILE=mesh1 METHOD=automatic
```

```
# Turn off heaters afterward
```

```
TURN_OFF_HEATERS
```